



Product description

Model with monitoring contact as potential-free changeover contact, actuated by the latch bolt.

Overview of Advantages

- Radius keeper, FaFix®, adjustable by 3 mm
- Universal voltage
- Compatible with current mortise locks
- Compatible with available striking plates
- Symmetrical design. DIN left/right as well as horizontal applicable

Scope of delivery

- 1 piece electric strike

Technical data

Handing	Universal
potential	10-24 V AC/DC
Adjustable latch (FF, FaFix®)	Yes
Monitoring contact (RR)	Yes
Fail-locked	Yes
Continuous duty	11-13 V_DC
Rated resistance	43 Ohm
Switching capacity - monitoring contact	24 V / 1 A
Current consumption 12 V AC	250 mA
Current consumption 12 V DC	280 mA
Current consumption 24 V AC	500 mA
Current consumption 24 V DC	560 mA
Break-in resistance	3750 N
Height	74 mm
Width	16 mm
Depth	26 mm
FaFix® adjustment range	3 mm
Latch bolt engaging depth	5,5 mm
Operating temperature range	-15 °C to +40 °C
Installation position	Vertical and horizontal
Max. latch preload AC	200 N
Load cycles for in-plant test	250000
Suitable for fire doors	No
Max. latch preload DC (stabilised)	50 N
Max. latch preload DC (stabilised) 12 V	50 N

Article number	118RR- - - - - A71
EAN-Number	4042203340749

