

# IPC-CD1C20-0360B

## 2 MP IR Mini-Dome Network Camera



### PRODUCT OVERVIEW

EZ-IP is perfect for small to medium size applications like home/residential security, small retail shops, and other typical SMB applications. It offers a perfect alternative to migrate from analog to an IP system with its easy to use nature and cost effectiveness. EZ-IP is fully in line with Dahua's quality. Stable and reliable components are utilized and Various tests such as anti-vibration, water resistance, and aging tests are performed to ensure Dahua quality standards.

### FEATURES

- 1/2.7" 2 Megapixel progressive CMOS
- H.265+ & H.265 dual-stream encoding
- 25/30 fps @ 1080P (1920x1080)
- DWDR, Day/night (ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS
- 3.6 mm fixed lens
- Max IR LEDs Length 30 m
- IP67, PoE

### FUNCTIONS

#### Smart Codec (H.265+ & H.264+)

Smart Codec is the optimized implementation of standard video compression (H.265 & H.264) that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. Smart Codec technology reduces bit rate and storage requirements by up to 70% when compared to the standard video compression.

#### True Day/Night

A day/night mechanical IR cut filter makes this camera ideal for applications with fluctuating lighting conditions, delivering color images during the day and automatically switching to monochrome as the scene darkens

#### Regions of interest

Regions of Interest (ROI) is a user defined feature that allows the operator to monitor specific areas of a scene while still maintaining overall situational awareness of less important areas

#### Smart IR

With IR illumination, detailed images can be captured in low light or total darkness. The camera's Smart IR technology adjusts to the intensity of camera's infrared LEDs to compensate for the distance of an object. Smart IR technology prevents IR LEDs from whiting out images as they come closer to the camera. The camera's integrated infrared

illumination provides high performance in extreme low-light environments up to 30 m (98 ft).

#### Image flip

Capturing unnecessary data such as surrounding hallway walls can increase storage requirements without any added value. The image flip feature allows the camera's image to be rotated in 90° increments for better video optimization.

#### Environmental

Dahua cameras operate in extreme temperature environments, rated for use in temperatures from -30°C to +60°C (-22°F to +140°F) with 95% humidity.

#### Protection (IP67, wide voltage)

The camera allows for ±25% input voltage tolerance, suitable for the most unstable conditions for outdoor applications. Its 2kV lightning rating provides effective protection for both the camera and its structure against lightning. Subjected and certified to rigorous dust and immersion tests (IP67).

#### Interoperability

The camera conforms to the ONVIF (Open Network Video Interface Forum) specifications, ensuring interoperability between network video products regardless of manufacturer.

## TECHNICAL SPECIFICATION

## Camera

|                      |   |
|----------------------|---|
| Image Sensor         | 1/2.7" 2 Megapixel progressive CMOS   |
| Effective Pixels     | 1920 (H) x 1080 (V)   |
| RAM/ROM              | 64MB/16MB   |
| Scanning System      | Progressive   |
| Minimum Illumination | 0.09 lx; f/2.0 (Color, 1/3 s, 30IRE)<br>0.5 lx; f/2.0 (Color, 1/30 s, 30IRE)<br>0 lx; f/2.0 (IR on) |
| S/N Ratio            | More than 50 dB   |
| IR Distance          | Distance up to 30 m (98 ft)   |
| IR On/Off Control    | Auto/manual   |
| IR LEDs              | 1   |

## Lens

|                      |        |                           |         |           |          |
|----------------------|--------|---------------------------|---------|-----------|----------|
| Lens Type            |        | Fixed                     |         |           |          |
| Mount Type           |        | Board-in                  |         |           |          |
| Focal Length         |        | 3.6 mm                    |         |           |          |
| Max. Aperture        |        | f/2.0; f/2.0              |         |           |          |
| Angle of View        |        | H: 115°/87.5°, V: 60°/47° |         |           |          |
| Focus Control        |        | Fixed                     |         |           |          |
| Close Focus Distance |        | 0.6 m (1.97 ft)           |         |           |          |
| DORI Distance        | Lens   | Detect                    | Observe | Recognize | Identify |
|                      | 3.6 mm | 53.3 m                    | 21.3 m  | 10.7 m    | 5.3 m    |

## PTZ

|                |   |
|----------------|---|
| Pan/tilt range | Pan: 0°~355°; Tilt: 0°~75°; Rotation: 0°~355° |
|----------------|---|

## Video

|                                      |  |
|--------------------------------------|--|
| Compression                          | H.265/H.264H/MJPEG (Sub Stream)  |
| Smart Codec                          | Support H.265+/H.264+  |
| Streaming Capability                 | 2 Streams  |
| Resolution                           | 1080P (1920×1080)/1.3M (1280×960)/720P (1280×720)/D1 (704×576/704×480)/VGA (640×480)/CIF (352×288/352×240) |
| Frame Rate                           | Main Stream: 1080P (1~25/30 fps)<br>Sub Stream: D1(1~25/30 fps)  |
| Bit Rate Control                     | CBR/VBR  |
| Bit Rate                             | H265:12K~6400K H.264:32K~8192K   |
| Day/night                            | Auto (ICR)/Color/b/w   |
| BLC Mode                             | BLC/HLC/DWDR   |
| White Balance                        | Auto/Natural/Street Lamp/Outdoor/Manual  |
| Gain Control                         | Auto/Manual  |
| Noise Reduction                      | 3D DNR   |
| Motion Detetion                      | Off/On (4 Zone, Rectangle)   |
| Region of Interest                   | Off/On (4 Zone)  |
| Electronic Image Stabilization (EIS) | N/A  |
| Smart IR                             | Support  |
| Digital Zoom                         | 16x  |

## Video

|                 |                            |
|-----------------|----------------------------|
| Flip            | 0°/90°/180°/270°           |
| Mirror          | Off/On                     |
| Privacy Masking | Off/On (4 Area, Rectangle) |

## Audio

|             |     |
|-------------|-----|
| Compression | N/A |
|-------------|-----|

## Network

|                     |  |
|---------------------|--|
| Ethernet            | RJ-45 (10/100Base-T)   |
| Protocol            | HTTP; TCP; ARP; RTSP; RTP; RTCP; UDP; DHCP; DNS; IPV4; NTP; Multicast; ICMP; TLS |
| Interoperability    | ONVIF Profile S&G  |
| Streaming Method    | Unicast/Multicast  |
| Max. User Access    | 10 Users/20 Users  |
| Edge Storage        | N/A  |
| Web Viewer          | IE, Chrome, Firefox, Safari  |
| Management Software | Smart PSS, DSS, DMSS   |
| Smartphone          | iOS, Android   |

## Certifications

|                |                       |
|----------------|-----------------------|
| Certifications | CE: (EN 60950:2000)   |
| FCC:           | FCC Part 15 Subpart B |

## Interface

|                 |     |
|-----------------|-----|
| Video Interface | N/A |
| Audio Interface | N/A |
| RS485           | N/A |
| Alarm           | N/A |

## Electrical

|                   |                                  |
|-------------------|----------------------------------|
| Power Supply      | DC 12 V, PoE (802.3af) (Class 0) |
| Power Consumption | <5.1 W                           |


## Environmental

|                      |   |
|----------------------|---|
| Operating Conditions | -30°C~+60°C (-22°F~+140°F)/Less than 95% RH |
| Storage Conditions   | -30°C~+60°C (-22°F~+140°F)/Less than 95% RH |
| Ingress Protection   | IP67  |
| Vandal Resistance    | N/A   |

## Construction

|              |                                  |
|--------------|----------------------------------|
| Casing       | Plastic                          |
| Dimensions   | Φ122 mm × 98.1 mm (4.8" x 3.86") |
| Net Weight   | 0.35 kg (0.77 lb)                |
| Gross Weight | 0.49 kg (1.08 lb)                |

## ACCESSORIES



PFA130-E



PFB203W



PFA152-E



PFA106



PFB220C








PFA200W

## Accessories

|          |   |
|----------|---|
| PFA130-E | Water-proof Junction box                  |
| PFB203W  | Water-proof Wall Mount Bracket            |
| PFA152-E | Pole Mount Bracket                        |
| PFA106   | Adapter Plate of Mini Dome Camera         |
| PFB220C  | Ceiling Mount Bracket of Mini Dome Camera |
| PFA200W  | Rain Shade of Dome Camera                 |

## DIMENSIONS (MM)



| Ceiling Mount   | Junction Mount   |
|---|--|
| PFA106 + PFB220C  | PFA130-E   |
|     |   |
| Wall mount  | Wall mount with rain shade   |
| PFB203W   | PFA200W  |
|    |  |
| Pole mount  |  |
| PFB203W + PFA152-E  |  |
|  |  |