

IS-4500 TCP/IP Video Door Phone System

Honeywell






- Overall Introduction

- Glamorous Look
- Quality · Design
- High Performance

- IS-4500 Specifications

- Product Introduction
- Functionality Characteristics
- Dimensions
- Connection

- IP Video Door Phone System Illustration

- Internet Structure
 - System Configuration
 - Product List
- 





Leader of Automation Control—Automation control technologies are one of the things Honeywell is known for. The smart home is right in our core area of expertise

Refined Workmanship— Hundred-year manufacturing process control standards from Honeywell to build an advanced, flexible and reliable digital visual intercom system


Leading Security Technology — Incorporating the professional-level intrusion alarm function to the intercom system to help create a safer living environment

A New Lifestyle — Your home and your loved ones are your most precious asset, so a home security and control system is one of the most important investments you'll ever make to bring a connected home

IP VDP INNOVATOR...



In Pursuit of Perfection.....

A background image showing three people (two men and one woman) looking towards the camera, overlaid with a semi-transparent black text box. The image is in grayscale.

frog™ Design — 16.5 mm ultra slim body designed by frog™, bringing you brand new visual experience; the elegant silver body color fits various interior designs

Quality Metal — High quality silver anodized aluminum back cover fits various interior decorating styles.


Glass Panel — Flat-screen vandal resistant glass, making scratches difficult to stay; just a few wipes can bring a glossy surface back and provide a brilliant look every day

HD Camera—2.0 Mega Pixel CMOS camera bringing the intercom into the new HD era



Engineering and Art Ingeniously Integrated...





Control Interface — Designed based on user experience study, nice and user-friendly. Backgrounds, icons and structure layouts with 1024X600 high resolution display are extremely intuitive. Wallpapers can be changed to whatever you like. Everything is simple, easy and enjoyable!

Seamless Installation — Fits seamlessly on the wall: users won't see any screws either in the front or from the side angle, making the flush mounting almost perfect. **Capacitive Touch Screen Technology** — Makes the operation more accurate, more responsive and more user-friendly.

Easy Integration-- Designed to be easily integrated with MoMas™ Honeywell Smart Home Systems, thus providing complex developers the infinite possibilities of expandable intelligent community solutions.

IS-4500 IP Video Door Phone



Flat-screen vandal resistant glass panel

2.0 Mega Pixel CMOS camera

High quality anodized aluminum back cover

Micro SD slot, plug and play

Emergency button

7" TFT LCD screen


Find out more about IS-4500.....

Communications-IS-4500

desktop

Security Scenario Shortcut

Screen Lock for
Cleaning




Key Function Shortcuts Tap to Call Security Guards and Management Center

communication



communication


Video and audio communication with neighbors



communication

No volume control Yes


Tap to call management center



Call security guards and management centre directly by tapping shortcuts

communication

Supports up to 8 subphones, subphone communication and door-open via subphones




record

Up to 30 visitor photo storage,
press arrow to preview



record

3 away voice messages, maximum 60 second each




record



Front/Back Door Monitoring

Security scenario shortcuts




security

When there exists the abnormal zone, alarm notice pops up and abnormal zone is indicated

The administrator device receives the alarm notice

Alarm buzzing both onsite and at the management center



Press 'Help' to send alarm notice and activate alarm buzzing at the management center




Can also get help by press the emergency buttons

Advanced intrusion protection configuration





security

Tap to activate protection zones, icons turn green




security

Set, change the password




Customization of bypassed zone under Away scenario



information

Concurrent information update



Offline, new messages, new visitors

22:38

2011-01-17 Monday

Weather forecast

Guard

Office

Security

Visitors



Call

Messages

Door

information

Tap to view bulletin board, dropdown to check up to 50 messages



information



information

Security Visitors Call Messages Elevator

Title

Content...

Bulletin

Expenses

My Messages

Security Visitors Call Messages Elevator


NO	Title	Date
1	Content1	2011-02-22
2		
3		
4		

Bulletin

Expenses

My Messages

elevator control



personalization


Only take seconds to personalize ring tones and background
from the collection in micro SD card
easy plug-and-play




personalization



Brightness control



Volume control



Screen lock for clean



IS-4500 Features Summary

Communication

- Communication between property owner and visitors
- Communication with neighbors
- Communication with property owners and security guards
- In-house inter-communication,
- Supports up to 8 sub phones
- Door striker release and management center call (HSP-2000C)
- Supports 2 door cameras
- Command center and building security guards communication
- Visitor triple identification (community/building/unit)
- Call forwarding and multi-level management
- Management center call shortcut on GUI

Video Monitoring

Public area monitoring via compatible models of IP cameras (lift lobby, mailbox zone, playground, parking lot, etc.)

Security

- Security scenario customization: Away/Home/Sleep
- 6 customized security zones, 2 24-hour protection zones (fire/gas), 2 emergency buttons
- System self-diagnostics, alarm for abnormal zones
- Password and time delay setup
- Bypassed zone under Away scenario
- Alarm popup on GUI and onsite alarm buzzing
- Concurrent management center notification and alarm buzzing
- 2 Emergence alarms: Silent alarm to notify security guards and management center without onsite emergency alarm sound, voice alarm to notify security guards and management center with onsite emergency alarm at the same time
- Fire alarm/gas leakage alarm/infrared sensor alarm SMS to 10 pre-set cell phone numbers supported by ISNET-P2-C.
- Front and back monitoring through door cameras

Access Control

- Triple visitor entry identification (community/building/apartment), supported by lobby phone and door cameras.

Information Service

- Time, date and weather forecast
- 50 community messages (bulletins)
- 50 expense messages
- 50 my messages

Storage

- Store up to 30 visitor photos for property owners and management center
- 3 away messages, each can reach to 60 seconds
- Home page visitor record and message notice

Elevator Control

- Standard TCP/IP protocol
- Support elevator control and authorization

Connection Diagram

Indoor Video Sub phone



12VDC

NB: Video signal amplifier is a must when more than two video sub phones are installed



Elevator controller



fire sensor*1




Emergency button



gas sensor*1



intrusion sensor*6



network switcher



door camera



door camera



electronic door striker (door camera)

TCP/IP elevator control

2*0.75mm² fire alarm

2*0.75mm² emergency help

3*0.75mm² gas leak alarm

8*0.75mm² alarm input

RJ45

网线

4*0.75mm² video/audio/power

4*0.75mm² video/audio/power

12VDC power line

2*1.5mm² relay-output

IS-7500 supports the relay outputs for both front and back door data receive/deliver/system reset module/power

5*0.75mm²

alternative to electronic door striker

wireless remote door striker



Internet Structure

Single Building



Port 5432 and 8021 need ISNet server authorization to connect to the internet



IP VDP INNOVATOR

TCP/IP Video Door Phone System